



GRILLES & OUTLETS

- Available with round spigots or rectangular sockets to fit all Monsoon ducting systems
- Various types for different applications
- External and internal options
- Choices for the wall, ceiling and roof
- Manufactured with UV stable materials to reduce colour fade
- Airbricks meet British Standard BS493
- Choice of colours
- Excellent air flow performance
- Easy to install



Monsoon manufacture a wide range of ventilation terminals to either let air in or out. Wall outlets are available with round spigots in 100, 125 and 150mm dia. or with rectangular sockets to connect to all Monsoon ducting systems and fans.

Monsoon provide options for internal or external use on the wall, ceiling or roof. There are various choices for different situations.

Gravity Flap Outlets are designed to provide a back draft barrier, but are not recommended for use in exposed locations.

Louvred Grilles can be used internally and externally are available with or without a flyscreen and provide excellent airflow performance.

Cowled Outlets supply exceptional protection against the effects of high winds and driving rain and include a damper flap to help reduce back drafts.

High Rise Round Cowled Outlets save time and money when installing on an upper floor or in a high rise building. This outlet can be installed from the inside out negating the need for dangerous ladders and scaffolding.

Brick Size Outlets are designed to fit in the wall and form part of the brick work. They can be used internally and externally.

Air Valves for both extract and supply are available and are particularly useful to achieve a balanced airflow.

All are designed to provide optimum airflow performance and for easy installation. They are manufactured in high quality impact resistant polystyrene. Pressure loss figures detailed in the product listings are exhaust rates, except in a few instances where an intake figure is also shown.

Most are available in four colours to complement common wall finishes and are made with UV stable materials to reduce colour fade.

Also available is a selection of ventilators for doors, worktops and plinths.

WALL OUTLET COLOURS









W = White

B = Brown

C = Beige (Cotswold Stone)

T = Terracotta





GRILLES & OUTLETS

100MM [4"] WALL OUTLETS

100MM I4	"I WALL OUT Cox Boxed		Description	Dimens Overall	sions mm Fitting	Airflow area mm²	Pre 15 l/s	ssure loss. 30 l/s	pa 60 l/s	System 100	PolyVent 225	EasiPipe/ThermaPipe 100	100mm Round Flexi Hose	100mm Rect. Flexi Hose
	4900 4901	44910* 44910*	Wall Outlet with Gravity Flaps Wall Outlet with Gravity Flaps	154 x 154 154 x 154	○ 100 ■ 110 x 54	7200 5770	9.2 13.2	10.8	11.4 11.8		/ ‡	√	✓	1
	4902 4903	44932* 44932*	Cowled Wall Outlet with Damp Cowled Wall Outlet with Damp		○ 100 ■ 110 x 54	7230 5800	6.7	12.5 16.7	41.6		√ ‡	✓	✓	✓
	4904 F4904 4905 F4905	n/a 44954* n/a 44954*	Louvred Grille Louvred Grille with Flyscreen as intake Louvred Grille Louvred Grille with Flyscreen	154 x 154 154 x 154 154 x 154 154 x 154	100100110 x 54110 x 54	6500 5850 5500 4950	2.0 9.9 6.7 4.1 20.0	7.9 37.1 <i>25.6</i> 15.9 75.9	30.4 138.7 97.1 61.6 288.2	√ †			✓ ✓	<i>y</i>
	4994	n/a	Louvred Grille with Internal Damper	154 x 154	O 100	5125	19.8	36.6	96.0	√ †	√ ‡	✓	✓	

- = internal dimension O = outer dimension
- * include both round spigot and rectangular socket and are only available in white and brown
- † With adapter ref 070.
- ‡ With adapter ref 2005.

125MM [5"] WALL OUTLETS

Supertube 125 0 125 6.7 9.9 5900 n/a Wall Outlet with Gravity Flaps 200 x 200 11200 12.7 1 Cowled Wall Outlet with Damper 200 x 200 0 125 11500 7.7 1 / 5.8 13.1 5902 n/a 200 x 200 0 125 11500 0.6 2.1 7.7 1 1 5904 n/a Louvred Grille 200 x 200 0 125 9200 2.0 7.1 24.6 1 1 V F5904 Louvred Grille with Flyscreen n/a 183 x 195 0 125 6600 19.8 1 1 32.4 73.2 500 Louvred Grille with Internal n/a Damper

† With adapter ref. 570.

O = outer dimension

125mm Round Flexi Hose EasiPipe/ThermaPipe 125





GRILLES & OUTLETS

150MM [6"] WALL OUTLETS

Product	Code Boxed Prepack		Description	Dimensi Overall	ensions mm Fitting		Airflow area mm²	Pressure loss.pa 15 l/s 30 l/s 60 l/s		MegaDuct 220	EasiPipe/Ther	150mm Roun		
	6900	n/a	Wall Outlet with Gravity Flaps	200 x 200	0	150	16000	5.9	8.5	11.4	√ †	✓	1	
	6902	n/a	Cowled Wall Outlet with Dam	_{pe} 200 x 200	0	150	16500	5.3	8.0	14.5	√ †	1	1	
	6904 F6904	n/a n/a	Louvred Grille Louvred Grille with Flyscreen	200 x 200 200 x 200	0	150 150	16500 13200	0.5	1.8 5.2	6.3 17.4			1	

O = outer dimension

 \dagger = with adapter ref. 970 and ref. 135-6

